




SUNOVA SOLAR

Leading one-stop PV Supplier

HI-KILO

395-410W

High Efficiency Half-Cell Mono PERC Module (Full Black)



Excellent low irradiance performance.




Better light trapping and current collection to improve module power output and reliability.



Industry leading lowest thermal co-efficient of power.



Optimized electrical design and lower operating current for reduced hot spot loss and better temperature coefficient.




Certified to withstand:
wind load (2400 Pa) and
snow load (5400 Pa).



100% triple EL test
enabling remarkable reduction of
hidden crack rate of modules

LINEAR PERFORMANCE WARRANTY



15 years

Product quality &
process guarantee

25 years

Linear power
guarantee

0.55 %

Annual Degradation
Over 25 years

COMPREHENSIVE CERTIFICATES




ISO 9001: Quality Management System

ISO 14001: Environmental Management System Standard

ISO 45001: International Occupational Health and
Safety Assessment System Standard

* Different markets have different certification requirements. Also, the products are under rapid innovation.
Please confirm the certification status with regional sales representatives.

PERFORMANCE INSURANCE



中国平安

PING AN
P & C INSURANCE CO CN SZN

Make it happen

www.sunova-solar.com

ELECTRIC CHARACTERISTICS

Model of modules	SS-395-54MDH		SS-400-54MDH		SS-405-54MDH		SS-410-54MDH	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum power — P _{mp} (W)	395	294	400	298	405	302	410	305
Open-circuit voltage — V _{oc} (V)	36.98	34.82	37.18	34.95	37.33	35.09	37.68	35.42
Short-circuit current — I _{sc} (A)	13.30	10.80	13.39	10.85	13.44	10.89	13.59	11.01
Maximum power voltage — V _{mp} (V)	31.23	29.09	31.42	29.22	31.55	29.35	31.84	29.61
Maximum power current — I _{mp} (A)	12.65	10.19	12.74	10.21	12.84	10.29	12.88	10.31
Module efficiency — η _m (%)	20.2%		20.5%		20.7%		21.0%	
Power tolerance (W)	(0,+5)							
Maximum system voltage (V)	1500							
Maximum rated fuse current (A)	25							
Current operating temperature (°C)	-40~+85 °C							

STC (Standard Testing Conditions): Irradiance 1000W/m², Cell Temperature 25 °C, Spectra at AM1.5

NOCT (Nominal Operating Cell Temperature): Irradiance 800W/m², Ambient Temperature 20°C, Spectra at AM1.5, Wind at 1m/s

STRUCTURAL CHARACTERISTICS

Module dimensions (L*W*H)	1722 x 1134 x 30 mm (67.80 x 44.65 x 1.18 inch)
Weight	21.5 kg (47.40 lbs)
Number of cells	108 cells
Cell	PERC Monocrystalline 182x91 mm (7.17 x 3.58 inch)
Glass	Tempered, 3.2 mm AR, High transmittance, Low iron
Frame	Anodized aluminum alloy
Junction box	IP68, 3 diodes
Output wire	4.0 mm ² , wire length: 300mm/customized
Connector	MC4 Compatible
Mechanical load	Snow load: 5400 Pa / Wind load: 2400 Pa


TEMPERATURE RATINGS

Temperature coefficient (P_{max})	-0.35 %/°C
Temperature coefficient (V_{oc})	-0.27 %/°C
Temperature coefficient (I_{sc})	+0.05 %/°C
Nominal operating cell temperature	45±2 °C

PACKAGING CONFIGURATION


Container	40HQ
Quantity/pallet	36
Pallets/container	26
Quantity/container	936

MODULE DIMENSIONS (MM)



* The unmarked tolerance is ±1 mm
Length shown in mm

Current-Voltage & Power-Voltage Curves (400W)

Temperature Dependence of I_{sc} , V_{oc} , P_{max} 